

# MULTI-LAYER PAINT & VARNISH REMOVER

## TECHNICAL DATA

100% Methyl Chloride FREE

Contents	500 ml
VOC-content	Approximately 98% w/w
Colour	Transparent
Scent	Characteristic
Relative density at 20°C	1,25 g/ml
Yield	1,5 g/sec
Vapour pressure at 20°C	3 to 4 bar
Coverage	Approximately 0,8 m <sup>2</sup>



**OB1** Multi-Layer Paint & Varnish Remover is a revolutionary product to remove old layers of paint and lacquer on surfaces of stone, asphalt, metal and wood.

### PRODUCT CHARACTERISTICS

- Gel structure. Very effective.
- The aerosol should be stored at room temperature before use.
- Application temperature 5 – 30°C.
- Spray pattern approximately 8 centimetre wide.

### APPLICATION

Shake before use. Before use, test the compatibility of the surface. Apply generously and allow to take effect. The time to take effect depends on the quality and age of the paint or lacquer to be removed. Then, remove with a tool appropriate for this purpose. On stubborn deposits, you need to repeat the process.

### SHELF LIFE

See elsewhere on the packaging (exp.).

Available in all good painting and decorators centres

**ob1original.com**

**OB1**<sup>™</sup>  
JOB DONE

All information, including illustrations, is believed to be reliable. Users however, should independently evaluate the suitability of each product for their application. Siroflex Ltd makes no warranties of the accuracy or completeness of the information, and disclaims any liability regarding its use. Siroflex Ltd only obligations are those in the standard terms and conditions of sale of this product, and in no case will Siroflex Ltd be liable for any incidental, indirect or consequential damages arising from the sale, resale, use or misuse of this product.