

OB1 HEAT PROTECT 1200°C INSTANT FIRE CEMENT BLACK
Date: 21.12.2024

Replaces: N/A
Ref: 0640.0.BB/DL

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product Name OB1 HEAT PROTECT 1200°C INSTANT FIRE CEMENT BLACK

Pure substance/mixture Mixture

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use Sealant

Uses advised against None known

1.3. Details of the supplier of the safety data sheet

Company Name

Siroflex Limited
Dodworth Business Park
Dodworth, Barnsley
South Yorkshire, S75 3SP
Tel +44 (0)1226 771600 Fax +44 (0)1226 771601

Further information available from: www.ob1original.com

1.4. Emergency telephone number

United Kingdom + 44 (0) 1226 771600 (Office Hours Only)
Ireland **NPIC - National Poison Information Centre**
Members of the Public: +353 (0)1 8092166 (8.00 am to 10.00 pm - 7 days a week)
Healthcare Professionals: +353 (0)1 8092566 (24 hour service)
Europe 112

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

GB CLP (SI 2020/1567 as amended)

Skin corrosion/irritation	Category 2 - (H315)
Serious eye damage/eye irritation	Category 1 - (H318)

2.2. Label elements

Contains Silicic acid, sodium salt (MR >1.6-2.6)



Signal word
Danger

SAFETY DATA SHEET

OB1 HEAT PROTECT 1200°C INSTANT FIRE CEMENT BLACK
Date: 21.12.2024

Replaces: N/A
Ref: 0640.0.BB/DL

Hazard statements

H315 - Causes skin irritation.

H318 - Causes serious eye damage.

Precautionary Statements - EU (§28, 1272/2008)

P101 - If medical advice is needed, have product container or label at hand

P102 - Keep out of reach of children

P280 - Wear protective gloves and eye/face protection

P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

P310 - Immediately call a POISON CENTER or doctor

P302 + P352 - IF ON SKIN: Wash with plenty of water and soap

P501 - Dispose of contents/ container to an approved waste disposal plant

2.3. Other hazards

No information available.

PBT & vPvB

This mixture contains no substance considered to be persistent, bioaccumulating or toxic (PBT). This mixture contains no substance considered to be very persistent nor very bioaccumulating (vPvB).

SECTION 3: Composition/information on ingredients

3.1 Substances

Not applicable

3.2 Mixtures

Chemical name	EC No (EU Index No).	CAS No..	Classification according to Regulation (EC) No. 1272/2008 [CLP]	Specific concentration limit (SCL)	M-Factor	M-Factor (long-term)	REACH registration number
Crystobalite >25 - <40 %	238-455-4	14464-46-1	[B]	-	-	-	-
Silicic acid, sodium salt (MR >1.6-2.6) 10 - <20 %	215-687-4	1344-09-8	STOT SE 3 (H335) Skin Irrit. 2 (H315) Eye Dam. 1 (H318)	-	-	-	01-2119448725-31-XXXX
Quartz (fine fraction) 5 - <10 %	238-878-4	14808-60-7	STOT RE 1 (H372)	-	-	-	[5]
Quartz 0.1 - <0.3 %	238-878-4	14808-60-7	[B]	-	-	-	[5]

Full text of H- and EUH-phrases: see section 16

NOTE [5] - This substance is exempted from registration according to the provisions of Article 2(7)(a) and Annex V of REACH

Classification according to Regulation (EC) No. 1272/2008 [CLP] - Notes

[B] - Substance with a Community workplace exposure limit

Acute Toxicity Estimate

If LD50/LC50 data is not available or does not correspond to the classification category, then the appropriate conversion value from CLP Annex I, Table 3.1.2, is used to calculate the acute toxicity estimate (ATEmix) for classifying a mixture based on its components

SAFETY DATA SHEET

OB1 HEAT PROTECT 1200°C INSTANT FIRE CEMENT BLACK
Date: 21.12.2024

Replaces: N/A
Ref: 0640.0.BB/DL

Chemical name	EC No (EU Index No)	CAS No.	Oral LD50 mg/kg	Dermal LD50 mg/kg	Inhalation LC50 - 4 hour - dust/mist - mg/L	Inhalation LC50 - 4 hour - vapour - mg/L	Inhalation LC50 - 4 hour - gas - ppm
Crystobalite	238-455-4	14464-46-1	-	-	-	-	-
Silicic acid, sodium salt (MR >1.6-2.6)	215-687-4	1344-09-8	-	-	-	-	-
Quartz (fine fraction)	238-878-4	14808-60-7	-	-	-	-	-
Quartz	238-878-4	14808-60-7	-	-	-	-	-

This product does not contain candidate substances of very high concern at a concentration $\geq 0.1\%$ (Regulation (EC) No. 1907/2006 (REACH), Article 59)

SECTION 4: First aid measures

4.1. Description of first aid measures

General advice	If medical advice is needed, have product container or label at hand. Immediate medical attention is required. Show this safety data sheet to the doctor in attendance.
Inhalation	Remove to fresh air. Get medical attention immediately if symptoms occur.
Eye contact	Consult an ophthalmologist. Get immediate medical attention. Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Keep eye wide open while rinsing. Do not rub affected area.
Skin contact	Wash off immediately with soap and plenty of water for at least 15 minutes. Get medical attention if irritation develops and persists.
Ingestion	Rinse mouth. Never give anything by mouth to an unconscious person. Do NOT induce vomiting. Call a doctor.
Self-protection of the first aider	Avoid contact with skin, eyes or clothing. Wear personal protective clothing (see section 8).

4.2. Most important symptoms and effects, both acute and delayed

Symptoms	Irritating to skin. Burning sensation.
Effects of Exposure	No information available.

4.3. Indication of any immediate medical attention and special treatment needed

Note to doctors	No information available.
------------------------	---------------------------

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable Extinguishing Media	Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Unsuitable extinguishing media	Full water jet.

5.2. Special hazards arising from the substance or mixture

SAFETY DATA SHEET

OB1 HEAT PROTECT 1200°C INSTANT FIRE CEMENT BLACK
Date: 21.12.2024

Replaces: N/A
Ref: 0640.0.BB/DL

Specific hazards arising from the chemical No information available.

Hazardous combustion products Silicon dioxide.

5.3. Advice for firefighters

Special protective equipment and precautions for fire-fighters Firefighters should wear self-contained breathing apparatus and full firefighting turnout gear. Use personal protection equipment.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions Avoid contact with skin, eyes or clothing. Use personal protective equipment as required. Ensure adequate ventilation.

Other information Refer to protective measures listed in Sections 7 and 8.

For emergency responders Use personal protection recommended in Section 8.

6.2. Environmental precautions

Environmental precautions Prevent further leakage or spillage if safe to do so.

6.3. Methods and material for containment and cleaning up

Methods for containment Prevent further leakage or spillage if safe to do so.

Methods for cleaning up Take up mechanically, placing in appropriate containers for disposal.

Prevention of secondary hazards Clean contaminated objects and areas thoroughly observing environmental regulations.

6.4. Reference to other sections

Reference to other sections See section 8 for more information. See section 13 for more information.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes or clothing. Do not eat, drink or smoke when using this product. Take off contaminated clothing and wash it before reuse.

General hygiene considerations Avoid contact with skin, eyes or clothing. Wear suitable gloves and eye/face protection. Do not eat, drink or smoke when using this product.

7.2. Conditions for safe storage, including any incompatibilities

Storage Conditions Protect from frost. Keep away from food, drink and animal feedingstuffs. Keep containers tightly closed in a dry, cool and well-ventilated place. Store locked up. Keep out of the reach of children. Keep from freezing.

Recommended storage temperature Keep at temperatures between 10 and 35 °C. Do not freeze.

7.3. Specific end use(s)

Specific use(s)
Sealant.

SAFETY DATA SHEET

OB1 HEAT PROTECT 1200°C INSTANT FIRE CEMENT BLACK
Date: 21.12.2024

Replaces: N/A
Ref: 0640.0.BB/DL

Risk Management Methods (RMM) The information required is contained in this Safety Data Sheet.

Other information Observe technical data sheet.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure Limits

Chemical name	European Union	United Kingdom
Crystobalite 14464-46-1	TWA: 0.1 mg/m ³	TWA: 0.1 mg/m ³ STEL: 0.3 mg/m ³
Kaolin 1332-58-7	-	TWA: 2 mg/m ³ STEL: 6 mg/m ³
Silicic acid, sodium salt (MR >1.6-2.6) 1344-09-8	15 min TWA Mg/m ³	-
Quartz (fine fraction) 14808-60-7	TWA: 0.1 mg/m ³	TWA: 0.1 mg/m ³ STEL: 0.3 mg/m ³
Quartz 14808-60-7	TWA: 0.1 mg/m ³	TWA: 0.1 mg/m ³ STEL: 0.3 mg/m ³

Derived No Effect Level (DNEL) No information available

Derived No Effect Level (DNEL)

Silicic acid, sodium salt (MR >1.6-2.6) (1344-09-8)

Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
worker Long term Systemic health effects	Inhalation	5.61 mg/m ³	
worker Long term Systemic health effects	Dermal	1.59 mg/kg bw/d	

Quartz (14808-60-7)

Derived No Effect Level (DNEL)

Silicic acid, sodium salt (MR >1.6-2.6) (1344-09-8)

Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
Consumer Long term Systemic health effects	Inhalation	1.38 mg/m ³	
Consumer Long term Systemic health effects	Dermal	0.8 mg/kg bw/d	
Consumer Long term Systemic health effects	Oral	0.8 mg/kg bw/d	

Quartz (fine fraction) (14808-60-7)

Predicted No Effect Concentration (PNEC)

Predicted No Effect Concentration (PNEC)

Crystobalite (14464-46-1)

Silicic acid, sodium salt (MR >1.6-2.6) (1344-09-8)

SAFETY DATA SHEET

OB1 HEAT PROTECT 1200°C INSTANT FIRE CEMENT BLACK
Date: 21.12.2024

Replaces: N/A
Ref: 0640.0.BB/DL

Environmental compartment	Predicted No Effect Concentration (PNEC)
Freshwater	7.5 mg/l
Marine water	1 mg/l
Sewage treatment plant	348 mg/l

Quartz (fine fraction) (14808-60-7)

8.2. Exposure controls

Engineering controls Ensure adequate ventilation, especially in confined areas.

Personal protective equipment

Eye/face protection

Hand protection

Goggles. or. Face protection shield. Eye protection must conform to standard EN 166.
Wear suitable gloves. Recommended Use: Nitrile rubber. Butyl rubber. Glove thickness > 0.7mm. Ensure that the breakthrough time of the glove material is not exceeded. Refer to glove supplier for information on breakthrough time for specific gloves. The breakthrough time for the mentioned glove material is in general greater than 480 min. Gloves must conform to standard EN 374

Skin and body protection

Respiratory protection

Wear suitable protective clothing.
Provide adequate ventilation.

Environmental exposure controls Do not allow uncontrolled discharge of product into the environment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state Solid
Appearance Paste
Colour Black
Odour Characteristic.

<u>Property</u>	<u>Values</u>	<u>Remarks • Method</u>
Melting point / freezing point	0 °C	
Initial boiling point and boiling range	100 °C	
Flammability	No data available	
Flammability Limit in Air		None known
Upper flammability or explosive limits	No data available	
Lower flammability or explosive limits	No data available	
Flash point	No data available	
Autoignition temperature	No data available	
Decomposition temperature		None known
pH	No data available	
pH (as aqueous solution)	>= 12.5	solution (50 %)
Kinematic viscosity	> 21 mm ² /s	@ 40 °C
Dynamic viscosity	No data available	
Water solubility	Miscible in water.	
Solubility(ies)	No data available	
Partition coefficient	No data available	
Vapour pressure	23	hPa
Relative density	2	
Bulk density	No data available	
Density	1.95 - 2.05 g/cm ³	
Relative vapour density	No data available	
Particle characteristics		
Particle Size	No information available	
Particle Size Distribution	No information available	

9.2. Other information

Solid content (%) No information available
VOC content No data available

SAFETY DATA SHEET

OB1 HEAT PROTECT 1200°C INSTANT FIRE CEMENT BLACK
Date: 21.12.2024

Replaces: N/A
Ref: 0640.0.BB/DL

9.2.1. Information with regards to physical hazard classes
Not applicable

9.2.2. Other safety characteristics
No information available

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity Stable under recommended storage conditions.

10.2. Chemical stability

Stability Stable under normal conditions.

Explosion data

Sensitivity to mechanical impact None.

Sensitivity to static discharge None.

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions None under normal processing.

10.4. Conditions to avoid

Conditions to avoid Protect from frost. Do not freeze.

10.5. Incompatible materials

Incompatible materials Strong acids. Strong bases. Strong oxidising agents.

10.6. Hazardous decomposition products

Hazardous decomposition products None under normal use conditions. Stable under recommended storage conditions.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Information on likely routes of exposure

Product Information

Inhalation Based on available data, the classification criteria are not met. Specific test data for the substance or mixture is not available. May cause irritation of respiratory tract.

Eye contact Specific test data for the substance or mixture is not available. Causes serious eye damage. May cause irreversible damage to eyes.

Skin contact Specific test data for the substance or mixture is not available. Causes skin irritation. (based on components).

Ingestion Based on available data, the classification criteria are not met. Specific test data for the substance or mixture is not available. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhoea.

SAFETY DATA SHEET

OB1 HEAT PROTECT 1200°C INSTANT FIRE CEMENT BLACK
Date: 21.12.2024

Replaces: N/A
Ref: 0640.0.BB/DL

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms Redness. Burning. May cause blindness. May cause redness and tearing of the eyes.

Acute toxicity

Numerical measures of toxicity

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (oral)	>2000 mg/kg
ATEmix (dermal)	>2000 mg/kg
ATEmix (inhalation-gas)	>20000 ppm
ATEmix (inhalation-dust/mist)	>5 mg/l
ATEmix (inhalation-vapour)	>20 mg/l

Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Silicic acid, sodium salt (MR >1.6-2.6)	=3400 mg/kg (Rattus) (OECD 401)	> 4640 mg/kg (Oryctolagus cuniculus)	-
Quartz (fine fraction)	>2000 mg/kg (Rattus)	-	-
Quartz	>2000 mg/kg (Rattus)	-	-

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation Classification based on data available for ingredients. Causes skin irritation.

Serious eye damage/eye irritation Classification based on data available for ingredients. Causes burns. Causes serious eye damage.

Respiratory or skin sensitisation Based on available data, the classification criteria are not met.

Germ cell mutagenicity Based on available data, the classification criteria are not met.

Carcinogenicity Based on available data, the classification criteria are not met.

Reproductive toxicity Based on available data, the classification criteria are not met.

STOT - single exposure Based on available data, the classification criteria are not met.

STOT - repeated exposure This product contains crystalline silica (quartz) in a non-respirable form. Inhalation of crystalline silica is unlikely to occur from exposure to this product.

Aspiration hazard Based on available data, the classification criteria are not met.

11.2. Information on other hazards

11.2.1. Endocrine disrupting properties

SAFETY DATA SHEET

OB1 HEAT PROTECT 1200°C INSTANT FIRE CEMENT BLACK
Date: 21.12.2024

Replaces: N/A
Ref: 0640.0.BB/DL

Endocrine disrupting properties No information available.

11.2.2. Other information

Other adverse effects No information available.

SECTION 12: Ecological information

12.1. Toxicity

Ecotoxicity

Chemical name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea	M-Factor	M-Factor (long-term)
Silicic acid, sodium salt (MR >1.6-2.6) 1344-09-8	-	LC50 96 h 301 - 478 mg/L (Lepomis macrochirus)	-	EC50 96 h = 216 mg/L (Daphnia magna)		

12.2. Persistence and degradability

Persistence and degradability No information available.

12.3. Bioaccumulative potential

Bioaccumulation There is no data for this product.

12.4. Mobility in soil

Mobility in soil No information available.

12.5. Results of PBT and vPvB assessment

PBT and vPvB assessment The product does not contain any substance(s) classified as PBT or vPvB above the threshold of declaration.

Chemical name	PBT and vPvB assessment
Silicic acid, sodium salt (MR >1.6-2.6)	The substance is not PBT / vPvB

12.6. Endocrine disrupting properties

Endocrine disrupting properties No information available.

12.7. Other adverse effects

No information available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste from residues/unused products Dispose of contents/container in accordance with local, regional, national, and international regulations as applicable.

Contaminated packaging Handle contaminated packages in the same way as the product itself.

European Waste Catalogue 08 04 09* waste adhesives and sealants containing organic solvents or other dangerous

SAFETY DATA SHEET

OB1 HEAT PROTECT 1200°C INSTANT FIRE CEMENT BLACK
Date: 21.12.2024

Replaces: N/A
Ref: 0640.0.BB/DL

substances

Other information Waste codes should be assigned by the user based on the application for which the product was used.

SECTION 14: Transport information

Note: Keep from freezing.

Land transport (ADR/RID)

14.1 UN number or ID number	Not regulated
14.2 UN proper shipping name	-
14.3 Transport hazard class(es)	Not regulated
14.4 Packing group	Not regulated
14.5 Environmental hazards	Not applicable
14.6 Special precautions for user	
Special Provisions	None

IMDG

14.1 UN number or ID number	Not regulated
14.2 UN proper shipping name	Not regulated
14.3 Transport hazard class(es)	Not regulated
14.4 Packing group	Not regulated
14.5 Marine pollutant	NP
14.6 Special precautions for user	
Special Provisions	None
14.7 Maritime transport in bulk according to IMO instruments	
Transport in bulk according to Annex II of MARPOL and the IBC Code	Not applicable

Air transport (ICAO-TI / IATA-DGR)

14.1 UN number or ID number	Not regulated
14.2 UN proper shipping name	Not regulated
14.3 Transport hazard class(es)	Not regulated
14.4 Packing group	Not regulated
14.5 Environmental hazards	Not applicable
14.6 Special precautions for user	
Special Provisions	None

Section 15: REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

European Union

Take note of Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work

Check whether measures in accordance with Directive 94/33/EC for the protection of young people at work must be taken.

Take note of Directive 92/85/EC on the protection of pregnant and breastfeeding women at work

Registration, Evaluation, Authorisation, and Restriction of Chemicals (REACH) Regulation (EC 1907/2006)

SVHC: Substances of Very High Concern for Authorisation:

This product does not contain candidate substances of very high concern at a concentration $\geq 0.1\%$ (Regulation (EC) No. 1907/2006 (REACH), Article 59)

SAFETY DATA SHEET

OB1 HEAT PROTECT 1200°C INSTANT FIRE CEMENT BLACK
Date: 21.12.2024

Replaces: N/A
Ref: 0640.0.BB/DL

EU-REACH (1907/2006) - Annex XVII - Substances subject to Restriction

This product does not contain substances subject to restriction (Regulation (EC) No. 1907/2006 (REACH), Annex XVII).

Substance subject to authorisation per REACH Annex XIV

This product does not contain substances subject to authorisation (Regulation (EC) No. 1907/2006 (REACH), Annex XIV)

Export Notification requirements

This product does not contain substances which are regulated pursuant to Regulation (EC) No. 649/2012 of the European parliament and of the council concerning the export and import of dangerous chemicals above the level that triggers a labeling obligation under Regulation (EC) No 1272/2008. Therefore this product is not subject to prior informed consent notification.

Ozone-depleting substances (ODS) regulation (EC) 1005/2009

Not applicable

Persistent Organic Pollutants

Not applicable

REGULATION (EU) 2019/1148 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 20 June 2019 on the marketing and use of explosives precursors

Not applicable

National regulations

15.2. Chemical safety assessment

Chemical Safety Assessments have been carried out by the Reach registrants for substances registered at >10 tpa. No Chemical Safety Assessment has been carried out for this mixture

SECTION 16: Other information

Key or legend to abbreviations and acronyms used in the safety data sheet

Full text of H-Statements referred to under section 3

H315 - Causes skin irritation

H318 - Causes serious eye damage

H335 - May cause respiratory irritation

H372 - Causes damage to organs through prolonged or repeated exposure

Legend

TWA

TWA (time-weighted average)

STEL

STEL (Short Term Exposure Limit)

Ceiling

Ceiling Limit Value

Sk*

Skin designation

SVHC

Substance(s) of Very High Concern

PBT

Persistent, Bioaccumulative, and Toxic (PBT) Chemicals

vPvB

Very Persistent and very Bioaccumulative (vPvB) Chemicals

STOT RE

Specific target organ toxicity - Repeated exposure

STOT SE

Specific target organ toxicity - Single exposure

EWC

European Waste Catalogue

ADR

European Agreement concerning the International Carriage of Dangerous Goods by Road

IMDG

International Maritime Dangerous Goods (IMDG)

IATA

International Air Transport Association (IATA)

RID

Regulations concerning the International Transport of Dangerous Goods by Rail

SAFETY DATA SHEET

OB1 HEAT PROTECT 1200°C INSTANT FIRE CEMENT BLACK
Date: 21.12.2024

Replaces: N/A
Ref: 0640.0.BB/DL

Key literature references and sources for data

No information available

Prepared By Product Safety & Regulatory Affairs
Revision date 02-Aug-2024

Indication of changes

Revision note SDS sections updated, 11, 15.

Training Advice When working with hazardous materials, regular training of operators is required by law

Further information No information available

This SDS complies with the requirements of UK REACH Regulations SI 2019/758 (as amended)

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet